

**All Exhibitors****Submit before Sep. 29**

No.4 Water Supply and Drainage [Charge]

Exhibitor's Manual Page 37-38

To: FUKUDO KOGYO CO., LTD.

Date:

Exhibitor:	Booth No.
Contact: Mr./Ms. Section:	Management Office Use
TEL:	FAX:
E-mail:	

Do you need Water supply?	<input type="checkbox"/> Yes → Fill in the blanks below.	<input type="checkbox"/> No
---------------------------	--	-----------------------------

Note: Each hall has a room with hot-water server. If you only need hot water for serving tea and the like, no waterworks installation is required.

We hereby apply water supply and drainage as below.

1. Running Water (disposable)

Indicate the number of tap and drain port you would like to receive.

Supply Pipe Diameter		Number of Tap(s)	Total	
13 mm	¥77,000 (including tax)	×	¥	To set up 1 tap and drain port taking shortest path to water source
20 mm	¥90,750 (including tax)	×	¥	
25 mm	¥104,500 (including tax)	×	¥	

Note: Drainage pipes are available in 40 mm and 50 mm diameters.

- 1) Water supply pipes 30 mm in diameter or greater require a separate set of estimates.
- 2) In addition to the above, water usage fees apply to exhibitors who use running water (¥1,100/m³, including tax).
- 3) Hot-water drainage requires a separate estimate.
- 4) Please be sure to include a booth drawing clearly indicating the positions where water supply and drainage are required.

2. Circulation from Cooling Tower

Water volume required: Indicate your required water volume based on water-supply temperature of 20°C and water pressure of approximately 1 kg.

Closed Circulation	_____ liter/min. × ¥5,610 + ¥56,100 = ¥ _____ (including tax)
---------------------------	---

Breakdown

Device	Difference in Temperature of Water Supply and Drainage	Oil-cooler-type Coolant Water	Mold Coolant Water	Other	Total	24-hour Water Supply
Ex: Extruder	6 °C	4 L/min.	15 L/min.	2 L/min.	27 L/min.	<input type="checkbox"/> Required / <input type="checkbox"/> Not required
	°C	L/min.	L/min.	L/min.	L/min.	<input type="checkbox"/> Required / <input type="checkbox"/> Not required
	°C	L/min.	L/min.	L/min.	L/min.	<input type="checkbox"/> Required / <input type="checkbox"/> Not required
	°C	L/min.	L/min.	L/min.	L/min.	<input type="checkbox"/> Required / <input type="checkbox"/> Not required
	°C	L/min.	L/min.	L/min.	L/min.	<input type="checkbox"/> Required / <input type="checkbox"/> Not required
	°C	L/min.	L/min.	L/min.	L/min.	<input type="checkbox"/> Required / <input type="checkbox"/> Not required

- 1) If not enough paper forms are available, please write on photocopies.
- 2) If you have devices for which the temperature difference between water supply and drainage is 7°C or over, attach a copy of the appropriate device specification.
- 3) Please be sure to include a booth drawing clearly indicating the positions where water supply and drainage are required.

3. Overtime Water Supply and 24-hour Water Supply

If you need water supply beyond the standard supply hours (manual p. 37), please contact us separately.

Contact information of Contractor for Water Supply and Drainage Inside of the Booth	Contractor:	Person responsible:
	Address:	
	TEL: _____ FAX: _____	Registration No. of specified water contractor (issued by prefectural government in Japan) _____

- After your application is accepted, the contractor will send an estimate.
- If the address for sending the invoice is different from the exhibitor's, please contact the contractor separately.

Submit to**FUKUDO KOGYO CO., LTD. (Mr. Kataiwa / Mr. Ishikawa)**

5-32-18 Kameido, Koto-Ku, Tokyo 136-0071, JAPAN

TEL: +81-3-3638-0730 FAX: +81-3-3638-4937 E-mail: office@fukudo.co.jp